

# TP6-EC

## CUTTING AND BENDING MACHINE FOR AXIAL COMPONENTS



**23.OL01** STANDARD LEAD: 0,4 -1,3



**23.OL04** REINFORCED LEAD: 0,6 -1,4



**23.OL06** REDUCED LEAD: 0,4 -0,8

**23.OL07/09/10** REDUCED AND FIX PITCH LEAD Ø: 0,4 -0,6

The model TP6-EC is a manual machine, designed for cutting and bending taped axial components with lead diameter from 0,4 to 1,4mm (.015 to .055"). Operation quota are set up in a quick and precise manner. The high quality and reliability of this machine ensure the best operation for a very long time. No maintenance is required. This machine is only supplied manual version and for taped components.

PRODUCTION: 50000/HOUR

TP6/1-EC  
STANDARD - 23.OL01

	MM		IN	
	min	max	min	max
<b>P</b>	6,5	60	.255	2.362
<b>B</b>	4	13	.157	.511
<b>c</b>	1,2		.047	
<b>L</b>		50		1.968
<b>d</b>	0,4	1,3	.015	.051
<b>D</b>	0,4	16	.015	.629

TP6/4-EC  
REINFORCED - 23.OL04

	MM		IN	
	min	max	min	max
<b>P</b>	10,16	60	.4	2.362
<b>B</b>	5	13	.196	.511
<b>c</b>	2,4		.094	
<b>L</b>		50		1.968
<b>d</b>	0,6	1,4	.023	.055
<b>D</b>	0,6	16	.023	.629

TP6/6-EC  
REDUCED - 23.OL06

	MM		IN	
	min	max	min	max
<b>P</b>	5,08	60	.2	2.362
<b>B</b>	4	13	.157	.511
<b>c</b>	0,8		.031	
<b>L</b>		50		1.968
<b>d</b>	0,4	0,8	.015	.031
<b>D</b>	0,4	10	.015	.039

TP6/7-EC  
REDUCED FIX PITCH - 23.OL07

	MM		IN	
	min	max	min	max
<b>B</b>	4	10	.157	.393
<b>c</b>	0,5		.019	
<b>d</b>	0,4	0,6	.015	.023
<b>D</b>	0,4	4	.015	.157
<b>code 23.OL07</b>	<b>P</b>	5,08	.2	
<b>code 23.OL09</b>	<b>P</b>	7,62	.3	
<b>code 23.OL10</b>	<b>P</b>	10,16	.4	