

規格表



型號	扭力 (kgf. cm)	扭力 (Lbf. in)	扭力 (N. m)	空轉速 (r. p. m) HI
SKD-8300L	6~22	5.22~19.12	0.59~2.16	1000
SKD-8300P	6~22	5.22~19.12	0.59~2.16	1000
SKD-8400L	10~30	8.67~26.02	0.98~2.94	750
SKD-8400P	10~30	8.67~26.02	0.98~2.94	750
SKD-8500L	15~45	13.0~39.02	1.47~4.41	530
SKD-8500P	15~45	13.0~39.02	1.47~4.41	530
SKD-8300LF	5~12	4.34~10.44	0.49~1.18	2000
SKD-8300PF	5~12	4.34~10.44	0.49~1.18	2000

BSD-9500L is same with SKD-8500L.

Steel Collar Part No: CD91031-4 Coupler(Steel) 前鎖環 (Steel)

DC直流電壓全自動高扭力手按式、下壓式電動起子系列

SKD-8000L SKD-8000P

SKD-8000 系列

型號	扭力			空轉速(r.p.m)		適用螺絲直徑(mm)		重量 (g)	長度 (mm)	適用 電源控制棒	適用 起子頭
	(kgf.cm)	(Lbf.in)	(N.m)	HI	LO	機械牙	自攻牙				
SKD-8300L SKD-8300P	6-22	5.22-19.12	0.59-2.16	1000	700	2.6-4.0	2.0-3.5	700	269	SKP-32HL	A-B
SKD-8400L SKD-8400P	10-30	8.67-26.02	0.98-2.94	750	520	3.0-5.0	2.6-4.0	700	269	SKP-32HL	A-B
SKD-8500L SKD-8500P	15-45	13.0-39.02	1.47-4.41	530	360	4.0-6.0	3.0-5.0	700	269	SKP-32HL	A-B
SKD-8300LF SKD-8300PF	5-12	4.34-10.44	0.49-1.18	2000	---	2.0-3.0	2.0-2.6	700	269	SKP-32HL	A-B

#CE · RoHS